

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) A method of indicating a receipt of a stored message from a source,
the method comprising:

generating an information signal relating the stored message to at least one graphical image
associated with the source;

transmitting the information signal to a communications device associated with an addressee of
the stored message; and

indicating the receipt of the stored message in response to a receipt of the information signal by
the communications device.

2. (previously presented) A method according to claim 1, including generating a representation
of said at least one graphical image in the information signal.

3. (previously presented) A method according to claim 1, wherein said generating step includes:
identifying a network location where the at least one graphical image can be accessed by the
addressee; and
generating a representation of said network location in said information signal.

4. (previously presented) A method according to claim 3, including determining a network
address identifying said network location.

5. (previously presented) A method according to claim 1, wherein said transmitting step
includes transmitting said information signal for receipt by a network resource associated with
the addressee.

6. (previously presented) A method according to claim 1, including receiving notification that the stored message has been received.
7. (previously presented) A method according to claim 1, including storing the information signal for subsequent retrieval and transmission to the communications device.
8. (previously presented) A method according to claim 1, wherein said generating step includes generating said information signal in response to receipt of a signal indicating that the stored message has been received.
9. (previously presented) A method according to claim 1, including determining the source of the stored message.
10. (previously presented) A method according to claim 9, wherein said determining step includes determining a calling party associated with the stored message.
11. (previously presented) A method according to claim 9, wherein said determining step includes determining caller line identification information associated with the stored message.
12. (previously presented) A method according to claim 9, including requesting, from a networked device associated with the source, source information for associating the source with the at least one graphical image.
13. (previously presented) A method according to claim 12, including receiving the source information from the networked device and producing the information signal in said generating step using the source information.
14. (previously presented) A method according to claim 13, including storing the source information after said receiving step in a centrally located network resource associated with the addressee.

15. (previously presented) A method according to claim 12, wherein the receiving step includes receiving the at least one graphical image from the network device.

16. (previously presented) A method according to claim 1, wherein said generating step includes associating the at least one graphical image with a subscriber of a messaging system.

17. (previously presented) A method according to claim 1, wherein said generating step includes identifying a media type of the stored message and generating a representation of the media type in the information signal.

Ci 18. (previously presented) A method according to claim 17, including requesting data identifying the media type of the stored message from a network device associated with a subscriber.

19. (previously presented) A method according to claim 17, including encoding into the information signal a graphical image associated with the media type of the stored message.

20. (previously presented) A method according to claim 17, including encoding into the information signal data relating the stored message with a graphical image associated with the media type of the stored message.

21. (previously presented) A method according to claim 1, including transmitting the stored message to a networked communications device in response to a request for the stored message from the networked communications device.

22. (previously presented) A method according to claim 1, wherein in said transmitting step the information signal is transmitted to the communications device of the addressee in response to receiving a request for pending notifications from the addressee.

23. (previously presented) A method according to claim 1, including providing the source with at least one graphical image relating to the addressee before recording the stored message.

24. (previously presented) A method according to claim 1, including producing in the information signal a digital representation of a sound waveform associated with the source.

25. (previously presented) A method according to claim 1, including retrieving a digital representation of a sound waveform associated with the source and encoding the digital representation of the sound waveform in the information signal before transmitting the information signal to the communications device.

26. (previously presented) A method according to claim 1, including generating within said information signal a representation of at least one video frame from a stream of video data associated with the source.

C1 27. (previously presented) A method according to claim 1, wherein the stored message includes a stream of video data and said generating step includes producing within said information signal a representation of at least one video frame from the stream of video data.

28. (previously presented) A method according to claim 1, wherein the stored message includes a stream of video data and said generating step includes extracting the at least one graphical image from the stream of video data.

29. (previously presented) A method according to claim 1, including sending a control signal to a network resource for instructing the network resource to add at least a portion of the information represented within the information signal to 5 a web page accessible to the communications device.

30. (previously presented) A method according to claim 29, including notifying the communications device of a pending notification on the web page.

31. (previously presented) A method according to claim 1, including receiving a caller line related signal identifying subscriber information associated with a caller line from which the

stored message was received; and including at least a portion of the subscriber information in the information signal in said generating step.

32. (previously presented) A method according to claim 1, including relating the stored message to a pre-selected graphical image associated with the source and pre-selected by the source.

33. (previously presented) A method according to claim 1, including alerting the communications device that an incoming message from the source is being stored and permitting the communications device to interrupt the storage of the incoming message and connect with the source.

34. (previously presented) An apparatus for indicating a receipt of a stored message from a source, the apparatus comprising:

a generator configured to generate an information signal relating the stored message to at least one graphical image associated with the source;

a transmitter configured to initiate transmission of the information signal to a communications device associated with an addressee of the stored message; and

an indicator configured to indicate the receipt of the stored message in response to a receipt of the information signal by the communications device.

35. (previously presented) An apparatus according to claim 34, including a processor programmed to: (i) identify a network location where the at least one graphical image can be accessed by the addressee; and (ii) generate a representation of the network location within the information signal.

36. (previously presented) An apparatus according to claim 34, wherein said generator includes a message waiting notification server for producing the information signal.

37. (previously presented) An apparatus according to claim 34, including a processor programmed to initiate storage of at least a portion of the information within the information signal in a network resource.

38. (previously presented) An apparatus according to claim 34, including a computer server operative to communicate with a network resource where the at least one graphical image is stored.

39. (previously presented) An apparatus according to claim 38, wherein said transmitter is an integral component of said computer server.

40. (previously presented) An apparatus according to claim 34, including a receiver for receiving a request for a pending graphical notification from the addressee.

41. (previously presented) An apparatus according to claim 40, wherein said generator is programmed to process the request for a pending graphical notification.

42. (previously presented) An apparatus according to claim 41, wherein said transmitter is programmed to transmit the pending graphical notification to the communications device in the form of the information signal.

43. (previously presented) An apparatus according to claim 34, including a processor programmed to process a request from the communications device for the stored message.

44. (previously presented) An apparatus according to claim 34, including a processor programmed to process a representation of the at least one graphical image for inclusion in the information signal.

45. (previously presented) An apparatus according to claim 44, wherein said processor is programmed to generate the representation of the at least one graphical image.

46. (previously presented) An apparatus according to claim 44, wherein said processor is programmed to retrieve the representation of the at least one graphical image.

47. (previously presented) An apparatus according to claim 34, wherein said transmitter includes a processor programmed to instruct the communications device to add at least a portion of the information signal to a web page accessible to an end-user display device associated with the addressee.

C1 48. (previously presented) An apparatus according to claim 34, wherein said generator includes a processor programmed to (i) identify a media type of the stored message, and (ii) include a digital image associated with the media type in the information signal.

49. (previously presented) An apparatus according to claim 34, including a processor programmed to reproduce within said information signal a representation of at least one video frame from a video stream associated with the source.

50. (previously presented) A system including the apparatus claimed in claim 34, and further comprising:

a network computer operative to receive an incoming signal associated with the stored message and to initiate generation of the information signal with said generator in response to the incoming signal.

51. (previously presented) A system according to claim 50, wherein the network computer is programmed to communicate with the communications device via a network connection.

52. (previously presented) (previously presented) A system according to claim 51, including the communications device.

53. (previously presented) A system according to claim 52, wherein the communications device includes a processor programmed to receive and display the at least one graphical image.

54. (previously presented) A system according to claim 53, wherein the processor is programmed to receive the at least one graphical image from the network computer.

55. (previously presented) A system according to claim 53, wherein the processor is programmed to: (i) retrieve from the information signal a network location identifying where the at least one graphical image can be accessed; and (ii) retrieve from a network device located at the network location the at least one graphical image for display to the addressee.

56. (previously presented) A computer readable medium including codes for:

C1 (a) directing a network computer to generate an information signal relating a stored message to at least one graphical image associated with a source of the stored message; and

(b) directing the network computer to transmit the information signal to a communications device associated with an addressee of the stored message to indicate the receipt of the stored message.

57. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to produce a representation of said at least one graphical image in the information signal.

58. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to (i) identify a network location where the at least one graphical image can be accessed by the addressee, and (ii) generate a representation of said network location in the information signal.

59. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to (i) retrieve a network address identifying a network location where the at least one graphical image can be accessed and (ii) provide the network address in the information signal.

60. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to transmit the information signal to a network resource associated with the addressee.

61. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to initiate storage of at least a portion of the information signal for subsequent retrieval and transmission to the communications device.

62. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to determine the source of the stored message.

C

63. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to determine a calling party associated with the stored message.

64. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to determine a caller line associated with the stored message.

65. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to: (i) identify a media type of a stored message, and (ii) produce a representation of a graphical image associated with the media type in the information signal.

66. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to transmit the stored message to the communications device in response to a request for the stored message from the addressee.

67. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to transmit the information signal to the

communications device in response to the network computer receiving a request for pending notifications from the addressee.

68. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to: (i) retrieve a digital representation of a sound waveform associated with the source, and (ii) encode the digital representation of the sound waveform in the information signal before transmission of the information signal to the communications device.

C1 69. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to reproduce within said information signal a representation of at least one video frame from a video stream associated with the source.

70. (previously presented) A computer readable medium according to claim 56, wherein said codes include codes for directing the network computer to: (i) transmit a control signal to a network resource for instructing the network resource to add at least a portion of the information represented in the information signal to a web page accessible to the communications device.

71. (previously presented) A computer readable medium according to claim 56, including codes for directing the network computer to relate the stored message to a pre-selected graphical image associated with the source and pre-selected by the source.

72. (previously presented) A computer readable medium according to claim 56, including codes for directing the network to alert the communications device that an incoming message from the source is being stored and permitting the communications device to interrupt the storage of the incoming message and connect with the source.

73. (previously presented) A method of indicating receipt of a stored message from a source, the method comprising:

generating an information signal relating the stored message to at least one of: (i) a graphical image associated with the source; and (ii) a digital representation of a sound waveform associated with the source;

transmitting the information signal to a communications device associated with an addressee of the stored message; and

indicating the receipt of the stored message in response to a receipt of the information signal by the communications device.

C1

74. (previously presented) A method according to claim 73, wherein said generating step includes relating, within the information signal, the stored message to a plurality of graphical images associated with the source.

75. (previously presented) A method according to claim 73, wherein said generating step includes relating, within the information signal, the stored message to a plurality of digital representations of sound waveforms associated with the source.

76. (previously presented) A method according to claim 73, wherein the stored message includes a stream of video data and said generating step includes producing within said information signal a digital representation of a plurality of video frames captured from the stream of video data so as to include within said information signal a video notification associated with the source.

77. (previously presented) A method according to claim 76, wherein the stream of video data includes audio data and wherein the digital representation of the at least one sound waveform is captured from said audio data.